

GAGE ASSEMBLY COMPANY

Specifications and Gaging Lengths Cylindrical Steel Plug Gages



Taper Lock Design .125 — 1.510

HANDLE SIZE	SIZE RANGE		GAGING LENGTH		LENGTH HANDLE	LENGTH OVERALL	SIZE HEX
	ABOVE	TO AND INCL.	GO	NO GO			
00	.125	.150	3/8"	7/32"	1-3/4"	2-25/32"	1/4"
0	.150	.230	13/32"	9/32"	2"	3-3/16"	5/16"
1	.230	.365	3/4"	5/16"	2-3/4"	4-5/16"	3/8"
2	.365	.510	1"	3/8"	3"	4-7/8"	1/2"
3	.510	.825	1-1/4"	1/2"	3-1/4"	5-1/2"	11/16"
4	.825	1.135	1-1/2"	5/8"	3-5/8"	6-3/8"	7/8"
5	1.135	1.510	1-5/8"	3/4"	4"	7-1/8"	1"



Trilock Design Single or Double End .760 — 8.010

HANDLE SIZE	SIZE RANGE		GAGING LENGTH		LENGTH HANDLE	SIZE HEX
	ABOVE	TO AND INCL.	GO	NO GO		
2-1/2	.760	.947	1-1/4"	3/4"	4"	1/2"
3-1/2	.947	1.135	1-3/8"	3/4"	4"	5/8"
4-1/2	1.135	1.510	1-1/2"	3/4"	4"	13/16"
5-1/2	1.510	2.010	1-7/8"	7/8"	4-1/2"	1"
6	2.010	2.510	2"	7/8"	5"	1-1/8"
7	2.510	3.510	2"	1"	6"	1-1/4"
7	3.510	8.010	2-1/8"	1"	6"	1-1/4"



Progressive Design .125 — 4.510

HANDLE SIZE	SIZE RANGE		GAGING LENGTH		LENGTH HANDLE	LENGTH OVERALL	SIZE HEX
	ABOVE	TO AND INCL.	GO	NO GO			
00	.125	.150	3/8"	7/32"	1-3/4"	2-23/32"	1/4"
0	.150	.230	13/32"	9/32"	2"	3-1/16"	5/16"
1	.230	.365	3/4"	5/16"	2-3/4"	4-1/16"	3/8"
2	.365	.510	1"	3/8"	3"	4-5/8"	1/2"
3	.510	.825	1-1/4"	1/2"	3-1/4"	5-1/4"	11/16"
4	.825	1.135	1-3/8"	5/8"	3-5/8"	5-15/16"	7/8"
5	1.135	1.510	1-1/2"	3/4"	4"	6-5/8"	1"
6	*1.510	2.010	1-7/8"	7/8"	5"	7-7/8"	1-1/8"
6	2.010	2.510	2"	7/8"	5"	8"	1-1/8"
7	2.510	3.510	2"	1"	6"	9-1/8"	1-1/4"
7	3.510	4.510	2-1/8"	1"	6"	9-1/4"	1-1/4"

* Over 1.510 Trilock Design